

LM Laser Distance Sensor, Class 2. IP67, Pigtail M12 QD		IO-Link
LM IO-Link, Discrete and 4-20 mA, 50—150 mm		LM150KIQP
LM Mounting Brackets		
Base mount		SMBLML1
Rear mount		SMBLML2

Q4X Threaded Barrel, IO-Link and Dual Discrete		IO-Link
Q4X Dual Discrete & IO-Link, 25 to 100 mm		Q4XTKLAF100-Q8
Q4X Dual Discrete & IO-Link, 25 to 300 mm		Q4XTKLAF300-Q8
Q4X Dual Discrete & IO-Link, 25 mm to 600 mm		Q4XTKLAF600-Q8
Q4X Flat Face, IO-Link and Dual Discrete		IO-Link
Q4X Dual Discrete & IO-Link, 35 to 110 mm		Q4XFKLAF110-Q8
Q4X Dual Discrete & IO-Link, 35 to 310 mm		Q4XFKLAF310-Q8
Q4X Dual Discrete & IO-Link, 35 mm to 610 mm		Q4X FKLAF610-Q8
<i>For analog models with 4-20 mA output, change K to I: Q4XTILAF300-Q8</i>		
<i>For analog models with 0-10 V output, change K to U: Q4XTULAF300-Q8</i>		

Thread-on Lens Protector		
18 mm diameter, BSG—Borosilicate Glass window		APG18S
Swivel brackets		
Q4X Swivel bracket c/w bolt 3/8-16x2"		SMBQ4XFA
Q4X Swivel bracket c/w bolt M10-1.5x50		SMBQ4XFAM10
Q4X Swivel bracket no bolt, use 1/2", 12mm rods		SMBQ4XFAM12

LE IO-Link and Dual Discrete		IO-Link
LE Laser IO-Link and Dual Discrete, 100—400 mm		LE250KQ
LE Laser IO-Link and Dual Discrete, 100—1000 mm		LE 550KQ
LE Analog & Discrete		
LE Laser 4-20mA & PNP, 100—400 mm		LE250IQ
LE Laser 4-20mA & PNP, 100—1000 mm		LE550IQ
<i>For models with 15 cm pigtail M12 QD, add P to model: LE250KQP</i>		
<i>For models with analog 0-10V, change model from I to U: LE250UQ</i>		
<i>For models with Class 1 Laser, insert C1: LE550KC1Q</i>		
<i>AMS Brackets, compatible with NAAMS: 25 mm centers, 90° adjustment</i>		
LE Flat Plate AMS bracket		SMBAMSLTFP
LE Flat Plate AMS bracket, protective cover, c/w 2—BSG protective windows		SMBAMSLEIP
Replacement BSG—Borosilicate Glass window		RWAMSLE
AMS Base Right-angle bracket		SMBAMSBRA
Swivel		
LE Swivel bracket c/w 3/8" bolt		SMBLEFA
Cord adapter		
I/O block cord adapter. Allows remote teach via Pin 2		MQDC-5401SS-800753

Q5X Laser Distance Sensor, Class 2. IP67, Integral M12 QD		IO-Link
Q5X IO-Link & Dual Discrete, 95 mm—2000 mm	Q5XKLAFL2000-Q8	
AMS Brackets, compatible with NAAMS: 25 mm centers, 90° adjustment		
Q5X Flat Plate AMS bracket, protective cover, BSG protective window	SMBAMSQ5XIPP	
Q5X Right-angle AMS bracket, protective cover, BSG protective window	SMBAMSQ5XIPRA	
Q5X Flat Plate AMS bracket	SMBAMSQ5XP	
Q5X Right-angle AMS bracket	SMBAMSQ5XRA	
Replacement BSG—Borosilicate Glass window, qty 1	RWSMBQ5XIP-1	
Swivel Brackets, tilt & pan		
Q5X Swivel bracket, c/w bolt M10-1.5x50	SMBQ5XFAM10	
Fixed Mounts		
M4 Fixing Plate for rear mounting	SMBQ5XM4F	
Clamp bracket mounts to sensor dovetail	SMBQ5XDT	

Start with the Q4X

